

Network Working Group
Request for Comments: 5350
Updates: 2113, 3175
Category: Standards Track

J. Manner
TKK
A. McDonald
Siemens/Roke
September 2008

IANA Considerations for the IPv4 and IPv6 Router Alert Options

Status of This Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The IETF Trust (2008).

Abstract

This document updates the IANA allocation rules and registry of IPv4 and IPv6 Router Alert Option Values.

Table of Contents

1. Introduction	2
2. Use of the Router Alert Option Value Field	2
3. IANA Considerations	4
3.1. IANA Considerations for IPv4 Router Alert Option Values	4
3.2. IANA Considerations for IPv6 Router Alert Option Values	5
4. Security Considerations	5
5. Acknowledgements	6
6. References	6
6.1. Normative References	6
6.2. Informative References	6

1. Introduction

The IP Router Alert Option is defined for IPv4 in [RFC2113]. A similar IPv6 option is defined in [RFC2711]. When one of these options is present in an IP datagram, it indicates that the contents of the datagram may be interesting to routers. The Router Alert Option (RAO) is used by protocols such as the Resource Reservation Protocol (RSVP) [RFC2205] and IGMP [RFC3376].

Both the IPv4 and IPv6 options contain a two-octet Value field to carry extra information. This information can be used, for example, by routers to determine whether or not the packet should be more closely examined by them.

There can be up to 65536 values for the RAO. Yet, currently there is only a registry for IPv6 values. No registry or allocation policies are defined for IPv4.

This document updates the IANA registry for managing IPv4 and IPv6 Router Alert Option Values, and removes one existing IPv6 Router Alert Option Value.

2. Use of the Router Alert Option Value Field

One difference between the specifications for the IPv4 and IPv6 Router Alert Options is the way values for the Value field are managed. In [RFC2113], the IPv4 Router Alert Option Value field has the value 0 assigned to "Router shall examine packet". All other values (1-65535) are reserved. Neither a management mechanism (e.g., an IANA registry) nor an allocation policy are provided for the IPv4 RAO values.

The IPv6 Router Alert Option has an IANA-managed registry [IANA-IPv6RAO] containing allocations for the Value field.

In [RFC3175], the IPv4 Router Alert Option Value is described as a parameter that provides "additional information" to the router in making its interception decision, rather than as a registry managed by IANA. As such, this aggregation mechanism makes use of the Value field to carry the reservation aggregation level. For the IPv6 option, IANA has assigned a set of 32 values to indicate reservation levels. However, since other registrations have already been made in that registry, these values are from 3-35 (which is actually a set of 33 values).

Although it might have been desirable to have the same values used in both the IPv4 and IPv6 registries, the initial allocations in [RFC2711] and the aggregation-level allocations in [RFC3175] have

made this impossible. The following table shows the allocations in the IPv6 registry and the values used in the IPv4 registry, where the latter have been deduced from [RFC2113] and [RFC3175] with the assumption that the number of aggregation levels can be limited to 32 as in the IPv6 case. Entries for values 6 to 31 have been elided for brevity.

Value	IPv4 RAO Meaning	IPv6 RAO Meaning
0	Router shall examine packet [RFC2113] [RFC2205] [RFC3376] [RFC4286]	Datagram contains a Multicast Listener Discovery message [RFC2711] [RFC2710] [RFC4286]
1	Aggregated Reservation Nesting Level 1 [RFC3175]	Datagram contains RSVP message [RFC2711] [RFC2205]
2	Aggregated Reservation Nesting Level 2 [RFC3175]	Datagram contains an Active Networks message [RFC2711] [Schwartz2000]
3	Aggregated Reservation Nesting Level 3 [RFC3175]	Aggregated Reservation Nesting Level 0 [RFC3175](*)
4	Aggregated Reservation Nesting Level 4 [RFC3175]	Aggregated Reservation Nesting Level 1 [RFC3175]
5	Aggregated Reservation Nesting Level 5 [RFC3175]	Aggregated Reservation Nesting Level 2 [RFC3175]
...
32	Aggregated Reservation Nesting Level 32 [RFC3175]	Aggregated Reservation Nesting Level 29 [RFC3175]
33	Reserved	Aggregated Reservation Nesting Level 30 [RFC3175]
34	Reserved	Aggregated Reservation Nesting Level 31 [RFC3175]
35	Reserved	Aggregated Reservation Nesting Level 32(*) [RFC3175]
36-65534	Reserved	Reserved to IANA for future assignment
65535	Reserved	Reserved [IANA-IPv6RAO]

Note (*): The entry in the above table for the IPv6 RAO Value of 35 (Aggregated Reservation Nesting Level 32) has been marked due to an inconsistency in the text of [RFC3175], and is consequently reflected

in the IANA registry. In that document, the values 3-35 (i.e., 33 values) are defined for nesting levels 0-31 (i.e., 32 levels). Similarly, value 3 is a duplicate, because aggregation level 0 means end-to-end signaling, and this already has an IPv6 RAO value "1" assigned.

Also note that nesting levels begin at 1 for IPv4 (described in Section 1.4.9 of [RFC3175]) and 0 for IPv6 (allocated in Section 6 of [RFC3175]).

Section 3.2 of this document redefines these so that for IPv6, value 3 is no longer used and values 4-35 represent levels 1-32. This removes the above inconsistencies.

3. IANA Considerations

This section contains the new procedures for managing IPv4 Router Alert Option Values. IANA has created a registry for IPv4 Router Alert Option Values (described in Section 3.1) and has updated the IPv6 Router Alert Option Values (described in Section 3.2).

IP Router Alert Option Values are currently managed separately for IPv4 and IPv6. This document does not change this, as there is little value in forcing the two registries to be aligned.

3.1. IANA Considerations for IPv4 Router Alert Option Values

The Value field, as specified in [RFC2113], is two octets in length. The Value field is registered and maintained by IANA. The initial contents of this registry are:

Value	Description	Reference
0	Router shall examine packet	[RFC2113]
1-32	Aggregated Reservation Nesting Level	[RFC3175]
33-65502	Available for assignment by the IANA	
65503-65534	Available for experimental use	
65535	Reserved	

New values are to be assigned via IETF Review as defined in [RFC5226].

3.2. IANA Considerations for IPv6 Router Alert Option Values

The registry for IPv6 Router Alert Option Values continues to be maintained as specified in [RFC2711]. In addition, the following value has been removed from the IANA registry and reserved for possible future use (not to be allocated currently). The reason is that it is a duplicate value; aggregation level 0 means end-to-end signaling, and this already has an IPv6 RAO value "1" assigned.

Value	Description	Reference
3	RSVP Aggregation level 0	[RFC3175]

The following IPv6 RAO values are available for experimental use:

Value	Description	Reference
65503-65534	Experimental use	

4. Security Considerations

Since this document is only concerned with the IANA management of the IPv4 and IPv6 Router Alert Option Values registry, it raises no new security issues beyond those identified in [RFC2113] and [RFC2711].

Yet, as discussed in RFC 4727 [RFC4727], production networks do not necessarily support the use of experimental code points in IP option headers. The network scope of support for experimental values should be evaluated carefully before deploying any experimental RAO value across extended network domains, such as the public Internet. The potential to disrupt the stable operation of the network hosting the experiment through the use of unsupported experimental code points is a serious consideration when planning an experiment using such code points.

When experimental RAO values are deployed within an administratively self-contained network domain, the network administrators should ensure that each value is used consistently to avoid interference between experiments. When experimental values are used in traffic that crosses multiple administrative domains, the experimenters should assume that there is a risk that the same values will be used simultaneously by other experiments, and thus that there is a

possibility that the experiments will interfere. Particular attention should be given to security threats that such interference might create.

5. Acknowledgements

Thanks to Robert Hancock, Martin Stiernerling, Alan Ford, and Francois Le Faucheur for their helpful comments on this document.

6. References

6.1. Normative References

- [RFC2113] Katz, D., "IP Router Alert Option", RFC 2113, February 1997.
- [RFC2711] Partridge, C. and A. Jackson, "IPv6 Router Alert Option", RFC 2711, October 1999.
- [RFC3175] Baker, F., Iturralde, C., Le Faucheur, F., and B. Davie, "Aggregation of RSVP for IPv4 and IPv6 Reservations", RFC 3175, September 2001.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 5226, May 2008.

6.2. Informative References

- [IANA-IPv6RAO] "IANA Registry for Internet Protocol version 6 (IPv6) Router Alert Option Values", <<http://www.iana.org>>.
- [RFC2205] Braden, R., Ed., Zhang, L., Berson, S., Herzog, S., and S. Jamin, "Resource ReSerVation Protocol (RSVP) -- Version 1 Functional Specification", RFC 2205, September 1997.
- [RFC2710] Deering, S., Fenner, W., and B. Haberman, "Multicast Listener Discovery (MLD) for IPv6", RFC 2710, October 1999.
- [RFC3376] Cain, B., Deering, S., Kouvelas, I., Fenner, B., and A. Thyagarajan, "Internet Group Management Protocol, Version 3", RFC 3376, October 2002.
- [RFC4286] Haberman, B. and J. Martin, "Multicast Router Discovery", RFC 4286, December 2005.

- [RFC4727] Fenner, B., "Experimental Values In IPv4, IPv6, ICMPv4, ICMPv6, UDP, and TCP Headers", RFC 4727, November 2006.
- [Schwartz2000] Schwartz, B., Jackson, A., Strayer, W., Zhou, W., Rockwell, D., and C. Partridge, "Smart Packets: Applying Active Networks to Network Management", ACM Transactions on Computer Systems (TOCS), Volume 18, Issue 1, February 2000.

Authors' Addresses

Jukka Manner
Department of Communications and Networking (Comnet)
Helsinki University of Technology (TKK)
P.O. Box 3000
Espoo FIN-02015 TKK
Finland

Phone: +358 9 451 2481
EMail: jukka.manner@tkk.fi

Andrew McDonald
Roke Manor Research Ltd (a Siemens company)
Old Salisbury Lane
Romsey, Hampshire SO51 0ZN
United Kingdom

EMail: andrew.mcdonald@roke.co.uk

Full Copyright Statement

Copyright (C) The IETF Trust (2008).

This document is subject to the rights, licenses and restrictions contained in BCP 78, and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in BCP 78 and BCP 79.

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

